S-LINE

Charging Cables

Type 2, 16A

Product Information

Product Category	Cables
Compatibility	Type 2 to Type 2, 3-phase, 16 A, Mode 3
Current Rating	Max 16 A
Power Supply	3-phase
Operating Voltage	220 ± 10% AC
Protection Rating	IP54
Service Life	10,000 cycles
Operating Temperature	-40C° ~ + 55C°

Article Number	90220
Cable Length	3 m
Weight	Approx. 1,5 kg

Article Number	90604
Cable Length	5 m
Weight	Approx. 2,3 kg

Article Number	90605
Cable Length	7 m
Weight	Approx. 3 kg

Article Number	90606
Cable Length	10 m
Weight	Approx. 4,2 kg

Article Number	90609
Cable Length	15 m
Weight	Approx. 5,4 kg

Article Number	90610
Cable Length	20 m
Weight	Approx. 7,4 kg

- 11 kW charging capacity
- Built-in temperature monitoring
- Self-cleaning connectors that help prevent sparks
- 2-year warranty

SOLID AND STABLE

ENVIRONMETAL FRIENDLY

IP54 HIGH INGRESS PROTECTION

WATERPROOF

S-LINE

Charging Cables

Type 2, 32A

Produktinformation

Product Category	Cables
Compatibility	Type 2 to Type 2, 3-phase, 32 A, Mode 3
Current Rating	Max 32 A
Power Supply	3-phase
Operating Voltage	220 ± 10% AC
Protection Rating	IP54
Service Life	10,000 cycles
Operating Temperature	-40C° ~ + 55C°

Article Number	90217
Cable Length	3 m
Weight	Approx. 2 kg

Article Number	90601
Cable Length	5 m
Weight	Approx. 3,3 kg

Article Number	90602
Cable Length	7 m
Weight	Approx. 4,3 kg

Article Number	90603
Cable Length	10 m
Weight	Approx. 6,6 kg

Article Number	90607
Cable Length	15 m
Weight	Approx. 9,5 kg

Article Number	90608
Cable Length	20 m
Weight	Approx. 12,5 kg

- ↯ 11 kW charging capacity
- ↯ Built-in temperature monitoring
- ↯ Self-cleaning connectors that help prevent sparks
- ↯ 2-year warranty

SOLID AND STABLE

ENVIRONMETAL FRIENDLY

IP54 HIGH INGRESS PROTECTION

WATERPROOF

S-LINE

Charging Cables

Type 1, 16A

Product Information

Product Category	Cables
Compatibility	Type 1 to Type 2, 1-phase, 16 A, Mode 3
Current Rating	Max 16 A
Power Supply	1-phase
Operating Voltage	220 ± 10% AC
Protection Rating	IP54
Service Life	10,000 cycles
Operating Temperature	-40C° ~ + 55C°

Artikelnummer	90613
Kabellängd	5 m
Vikt	Approx. 1,8 kg

Artikelnummer	90614
Kabellängd	7 m
Vikt	Approx. 2,5 kg

Artikelnummer	90615
Kabellängd	10 m
Vikt	Approx. 3,3 kg

- 11 kW charging capacity
- Built-in temperature monitoring
- Self-cleaning connectors that help prevent sparks
- 2-year warranty

SOLID AND STABLE

ENVIRONMETAL FRIENDLY

IP54 HIGH INGRESS PROTECTION

WATERPROOF

S-LINE

Charging Cables

Coiled

Product Information

Product Category	Cables
Compatibility	Type 2 to Type 2, 3-phase, 16 A, Mode 3
Current Rating	Max 16 A
Power Supply	3-phase
Operating Voltage	220 ± 10% AC
Protection Rating	IP54
Service Life	10,000 cycles
Operating Temperature	-40C° ~ + 55C°

Article Number	90618
Cable Length	5 m
Weight	Approx. 2,6 kg

Article Number	90619
Cable Length	7 m
Weight	Approx. 3,1 kg

- 11 kW charging capacity
- Built-in temperature monitoring
- Self-cleaning connectors that help prevent sparks
- 2-year warranty